

Power supply unit (CV, DC) - MINI, CV, 24 V/4 W



Image similar

Prices

List price (excluding VAT)	9.95 EUR per 1
Minimum order quantity	1
Order step	1

Information

Item number	872128
EAN	4042943169747
Brand	 DEKOLIGHT

Description

- Flicker-free
- Secured against short circuits and overloads

Scope of Application

Features

Housing Material	Plastic
Housing Color	Black
Operating Mode	Constant voltage
Frequency	50 / 60 Hz
Inrush Current max.	5 A / 300 µs
Voltage range DC	176-250 V/DC
Warranty (years)	5
Power Factor	0.55
Max. units per MCB B10	35
Max. units per MCB B16	56
Max. units per MCB C10	74
Max. units per MCB C16	118
Primary Connection	With free strand / conductor ends
Secondary Connection	Open cables
Product weight Working	45 g

Temperature	-20 to 50 °C
Storage Temperature	-20 to 70 °C
Mounting Location	Outside
Mounting Location	Inside
Life Time	50000 h
Switching Cycles	100000
Rated Input Voltage	220-240 V/AC
Output Voltage	24 V/DC
Output Current in mA	0-170 mA
Output Current min. in mA	0 mA
Output Current max. in mA	170 mA
Power	4.0 W
Number of Channels	1
Protection Class	Protection class II /protective insulation
Length	53 mm
Width	27 mm
Height	21 mm
IP Protection Class	IP 65
Functions	Overtemperature protection
Functions	Overloading protection
Functions	Protective extra-low voltage
Functions	Furniture installation
Functions	Short-circuit proof
Functions	Lamp control gear 110

