

Datasheet

PROLED TURTLE CCU IP 65 ROUND

PROLED[®]

Article number: L5240712R
Article name: PROLED TURTLE CCU IP 65 ROUND
Article description: PROLED SWITCHING POWER SUPPLY TURTLE CCU IP65 ROUND 700-012
GTIN: 4251158429069



picture similar

Electrical properties:

Input:	
Voltage supply:	100 - 240 VAC ; 50 - 60 Hz ; 0.16 A
Inrush current:	< 5 A ; < 300 μs
Efficacy:	82 %
Power factor:	0,95
Output:	
Output:	700 mA CC; 6 - 17 VDC; 12 W
Output adjustable:	—

Technical properties:

Primary connection:	cable to open wires; 2 x 0.75 mm ²
Secondary connection:	cable to open wires; 2 x 0.82 mm ²
Control:	no
PWM dimmer:	—
Fan:	without fan

Date: 30.4.2024

Technical amendments and errors reserved.

PROLED[®]

MBN GmbH | Balthasar-Schaller-Str. 3 | 86616 Friedberg | Germany

Phone +49.821.60099-0 | Fax +49.821.60099-99

Central: info@proled.com | Internet: www.proled.com

Registered office of the company: Friedberg | Amtsgericht Augsburg HRB 19419 | Managing Director: Dr. Bernhard Steidl, Christian von Sassen

Protection properties:

Protections:	Short cut, Over power, Over temperature, Open circuit
Electrical safety class:	II
IP classification:	IP65
MM sign:	✓

Housing and size:

Size:	50 x 40 x 24 mm (l x w x h)
Housing colour:	white
Housing material:	Plastics
Product weight:	0,090 kg

Mounting instructions:

For outdoor use:	✓
Mounting place:	Stand mounting, Wall-ceiling mounting, Wall-ceiling installation
Mounting type:	screwable
Ambient temperature:	-20 °C to 50 °C
Max. case temperature:	80 °C

Flags: